AM640480G2TNQW02H AMPIRE 5.7 inch tft lcd module

Category Ampire Size 5.7" Resolution 640°480 Brightness 250 Contrast Ratio 250 : 1 Viewing Angle 70/70/50/50 Lamp Type WLED Signal Interface 40 pins Panel Type a-Si TFT-LCD, LCM Mass 0.500Kg Frame Rate 60 Active Area 115.2×86.4 Outline 127×98.43×6.9 Storage Temp -30 ~ 80 °C Operating Temp -20 ~ 70 °C Support Color 262K	Model	AM640480G2TNQW02H
Resolution 640*480 Brightness 250 Contrast Ratio 250 : 1 Viewing Angle 70/70/50/50 Lamp Type WLED Signal Interface 40 pins Panel Type a-Si TFT-LCD, LCM Mass 0.500Kg Frame Rate 60 Active Area 115.2×86.4 Outline 127×98.43×6.9 Storage Temp -30 ~ 80 °C Operating Temp -20 ~ 70 °C	Category	<u>Ampire</u>
Brightness 250 Contrast Ratio 250 : 1 Viewing Angle 70/70/50/50 Lamp Type WLED Signal Interface 40 pins Panel Type a-Si TFT-LCD, LCM Mass 0.500Kg Frame Rate 60 Active Area 115.2×86.4 Outline 127×98.43×6.9 Storage Temp -30 ~ 80 °C Operating Temp -20 ~ 70 °C	Size	5.7"
Contrast Ratio 250 : 1 Viewing Angle 70/70/50/50 Lamp Type WLED Signal Interface 40 pins Panel Type a-Si TFT-LCD, LCM Mass 0.500Kg Frame Rate 60 Active Area 115.2×86.4 Outline 127×98.43×6.9 Storage Temp -30 ~ 80 °C Operating Temp -20 ~ 70 °C	Resolution	640*480
Viewing Angle 70/70/50/50 Lamp Type WLED Signal Interface 40 pins Panel Type a-Si TFT-LCD, LCM Mass 0.500Kg Frame Rate 60 Active Area 115.2×86.4 Outline 127×98.43×6.9 Storage Temp -30 ~ 80 °C Operating Temp -20 ~ 70 °C	Brightness	250
Lamp Type WLED Signal Interface 40 pins Panel Type a-Si TFT-LCD, LCM Mass 0.500Kg Frame Rate 60 Active Area 115.2×86.4 Outline 127×98.43×6.9 Storage Temp -30 ~ 80 °C Operating Temp -20 ~ 70 °C	Contrast Ratio	250 : 1
Signal Interface 40 pins Panel Type a-Si TFT-LCD, LCM Mass 0.500Kg Frame Rate 60 Active Area 115.2×86.4 Outline 127×98.43×6.9 Storage Temp -30 ~ 80 °C Operating Temp -20 ~ 70 °C	Viewing Angle	70/70/50/50
Panel Type a-Si TFT-LCD, LCM Mass 0.500Kg Frame Rate 60 Active Area 115.2×86.4 Outline 127×98.43×6.9 Storage Temp -30 ~ 80 °C Operating Temp -20 ~ 70 °C	Lamp Type	WLED
Mass 0.500Kg Frame Rate 60 Active Area 115.2×86.4 Outline 127×98.43×6.9 Storage Temp -30 ~ 80 °C Operating Temp -20 ~ 70 °C	Signal Interface	40 pins
Frame Rate 60 Active Area 115.2×86.4 Outline 127×98.43×6.9 Storage Temp -30 ~ 80 °C Operating Temp -20 ~ 70 °C	Panel Type	a-Si TFT-LCD, LCM
Active Area 115.2×86.4 Outline 127×98.43×6.9 Storage Temp -30 ~ 80 °C Operating Temp -20 ~ 70 °C	Mass	0.500Kg
Outline127×98.43×6.9Storage Temp-30 ~ 80 °COperating Temp-20 ~ 70 °C	Frame Rate	60
Storage Temp -30 ~ 80 °C Operating Temp -20 ~ 70 °C	Active Area	115.2×86.4
Operating Temp -20 ~ 70 °C	Outline	127×98.43×6.9
	Storage Temp	-30 ~ 80 °C
Support Color 262K	Operating Temp	-20 ~ 70 °C
''	Support Color	262K

Note:

zylcdshop.com recommends that you inquire with the original factory or its agents about the latest production status and technical information about AM640480G2TNQW02H. The product parameters displayed on zylcdshop.com are entered by zylcdshop.com engineers according to the specifications, and efforts have been made to minimize errors, but we cannot guarantee the complete correctness of the parameters. Please refer to the specification sheet!

https://www.zylcdshop.com



https://www.zylcdshop.com